

# Nylon coated wire for hooks and eyes (Nylofix®)

Go for a longer and faster forming/dyeing run while maximizing the quality of the end product

## What can we offer you?

Round nylon coated low carbon steel wire for hooks and eyes.

Features	Benefits
<ul style="list-style-type: none"> <li>• Good dyability</li> <li>• High ductility</li> <li>• Excellent coating adhesion</li> <li>• Smooth surface</li> </ul>	<ul style="list-style-type: none"> <li>• Good formability</li> <li>• Homogeneous formation and dyeing</li> <li>• No peeling during the forming and sewing process. (ghost shifts possible)</li> <li>• No color variations over time</li> </ul>

## Product range

Nylofix®

Nominal coated wire Ø (mm)	Tensile strength (N/mm <sup>2</sup> )	Tolerance (mm)
0.80	675-825	+0.02/-0.01
0.84		+0.02/-0.01



Smooth surface



Available in a wide color range



No peeling during the forming and sewing process



No color variations over time

## Color range

Two standard base colors: White 111 and Black 911.  
Available color range: see the table below.  
Other colors available on customers request.

Color		Description	BJWP Code
	Black*	Black 911-6	B6
	Cappuccino	Cappucinno (Pantone643C)	C3
	Beige	Beige 2046	BT
	Apricot	Beige (Pantone4735C)	AP
	Skin color	Nude 201	N1
	Medium pink	Medium Pink (Pantone685C)	PM
	Pink I	Pink7060 (Pantone502C)	P7
	Pink II	Pink 2183 (Pantone182C)	P2
	Pale pink I	Pale Pink 7004 (Pantone691C)	P4
	Pale pink II	Pale Pink 705	PI
	White*	White 111-6	W6
	Gray-white*	White LoTi 1090	WL

(\*) Oeko-Tex® certified

**NEW** Bekaert anti-phenolic yellowing wire: a smooth coating with excellent anti-yellowing properties.

## Make-up

Make-up adapted to your needs

- Coil300: 20 kg coil
- FB250: 250kg spool
- FB500: 400kg spool



## Quality



**RoHS**  
compliant

### Modifications reserved

All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. © Bekaert 2016

 **BEKAERT**

**Bekaert Japan Co., Ltd.**  
3F, 2-27-10, Hatchobori,  
Chuo-ku  
Tokyo 104-0031  
Japan  
T +81 3 3243 2522  
F +81 3 3243 25 21  
info.jptok@bekaert.com

**Bekaert Management Co., Ltd**  
17F, Block E, Waterfront Place  
N°31, Lane 168, Daduhe Road  
200336 Shanghai  
China  
T +86 21 2219 7000  
F +86 21 2219 7399  
wire.china@bekaert.com

**Bekaert Singapore Pte Ltd**  
2 Havelock Road  
#10-01 Apollo Centre  
Singapore 059763  
T +65 6732 36 33  
F +65 6535 35 78  
sales.singapore@bekaert.com

**Bekaert Industries Private Ltd.**  
Sai Trinity Building  
Unit N° 9 & 20 -  
5th Floor, Central Wing- S.N°146,  
Pashan  
Pune - 411 021  
India  
T +91 20 6627 6600  
F +91 20 6627 6601  
steelwire.pune@bekaert.com

info@bekaert.com  
www.bekaert.com