

Guy Strand Datasheet

Guy strands secure many of the largest man-made structures, including power and telecommunications lines, railway signals, towers, masts and wind turbines. Provide reliable support with Bekaert steel guy strand. Bekaert offers a variety of strengths and coatings including ASTM A475 and ASTM A855.

Strand diameter (in)	Wires per strand	Coated wire diameter (in)	Approx. strand weight/1000 ft (lbs)	Minimum Breaking Strength (lbs)					Minimum weight of coating oz/ft ²			
				Utility grades	Common grade	Siemens-Martin Grade	High strength grade	Extra high strength grade	Class A	Class B	Class Bezinal® C	
3/16	7	0.062	73	...	1,150	1,900	2,850	3,990	0.50	1.00	1.50	0.50
3/16	7	0.065	80	2,400	...	...	...	...	0.50	1.00	1.50	0.50
7/32	7	0.072	98	...	1,540	2,560	3,850	5,400	0.50	1.00	1.50	0.50
1/4	3	0.120	117	3,150	1,860	3,040	4,730	6,740	0.85	1.70	2.55	0.85
1/4	3	0.120	117	4,500	...	...	...	...	0.85	1.70	2.55	0.85
1/4	7	0.080	121	...	1,900	3,150	4,750	6,650	0.60	1.20	1.80	0.60
9/32	7	0.093	164	4,600	2,570	4,250	6,400	8,950	0.70	1.40	2.10	0.70
5/16	3	0.145	171	6,500	2,490	4,090	6,350	9,100	0.90	1.80	2.70	0.90
5/16	7	0.104	205	...	3,200	5,350	8,000	11,200	0.80	1.60	2.40	0.80
5/16	7	0.109	225	6,000	...	...	...	...	0.80	1.60	2.40	0.80
3/8	3	0.165	220	8,500	3,330	5,560	8,360	11,800	0.90	1.80	2.70	0.90
3/8	7	0.120	273	11,500	4,250	6,950	10,800	15,400	0.85	1.70	2.55	0.85
7/16	7	0.145	399	18,000	5,700	12,100	14,500	20,800	0.90	1.80	2.70	0.90
1/2	7	0.165	517	25,000	7,400	9,350	18,800	26,900	0.90	1.80	2.70	0.90
1/2	19	0.100	504	...	7,620	12,700	19,100	26,700	0.70	1.40	2.10	0.70
9/16	7	0.188	671	...	9,600	15,700	24,500	3,500	1.00	2.00	3.00	1.00
9/16	19	0.113	637	...	9,640	16,100	24,100	33,700	0.80	1.60	2.40	0.80
5/8	7	0.207	813	...	11,600	19,100	29,600	42,400	1.00	2.00	3.00	1.00
5/8	19	0.125	796	...	11,000	18,100	28,100	40,200	0.85	1.70	2.55	0.85
3/4	19	0.150	1,155	...	16,000	26,200	40,800	58,300	0.90	1.80	2.70	0.90
7/8	19	0.177	1,581	...	21,900	35,900	55,800	79,700	0.90	1.80	2.70	0.90
1	19	0.200	2,073	...	28,700	47,000	73,200	104,500	1.00	2.00	3.00	1.00

1x3 Ground Wire, 5/16", Class C Grade BB, ASTM A111 and A475

ISO 14001
certified

ISO 9001
certified



Contact us

More
Information?

4300 Wildwood Parkway,
Suite 100
Marietta, Georgia 30339, USA
770.514.2219
www.bekaert.com/power-utilities



Modifications reserved.
All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. ©Bekaert 2022