



## Easy to process, looks good on the shelves

### Why choose Bekaert?

1

#### Flexible make-up

Bekaert paint roller wire is available in a wide range of make-ups and dimensions enabling smooth unwinding for an optimal production process.

2

#### Fast delivery

Bekaert is active in more than 120 countries. This enables us to produce and keep large stocks of Bekaert paint roller wire in most global regions. Thanks to our global presence we can offer wires of consistent quality and timely deliveries wherever they are situated.

3

#### Our expertise, your success

Bekaert has more than 130 years of experience in producing coated steel wires, giving us the flexibility and technical know-how to give the right technical support.

4

#### Certified quality

Bekaert paint roller wire holds the ISO 9001 certificate that guarantees the internationally recognized quality of our products.

# Paint roller wire

## What can we offer you?

A brilliant redrawn galvanized steel wire.

### Features

- Narrow diameter tolerance
- Uniform and consistent tensile strength
- Zinc coating

### Benefits

- Complies with strict diameter and form stability standards
- Increased productivity: Smooth production process and good formability
- Shiny and smooth surface

## Product range

### Hard ordinary galvanized wire for paint rollers (H.O.G.)

(Also available with additional wax coating)

	Diameter (mm)	Tensile strength (N/mm <sup>2</sup> )		
		Min	Max	
Hard grade I* (Final coated)	6.00	530	680	± 0.05
	8.00	520	670	± 0.06
Hard grade II	6.00	580	730	± 0.03
	8.00	570	720	± 0.04

(\*) On request diameter range 5.00 - 8.20 mm

### Soft ordinary galvanized wire for paint rollers (S.O.G.)

	Diameter (mm)	Tensile strength (N/mm <sup>2</sup> )		Diameter tolerance (mm)
		Min	Max	
Soft Grade I	6.00	450	600	± 0.03
	8.00	450	600	± 0.04
Soft Grade II*	6.00	500	650	± 0.03
	6.04	500	650	± 0.03
	7.00	500	650	± 0.04
	7.70	500	650	-0.05/+0.00
	8.00	500	650	± 0.04
	8.04	500	650	± 0.04

(\*) On request diameter range 5.00 - 8.00 mm

Would you like to know more about Bekaert's brilliant redrawn wire for paint rollers?

Feel free to contact us.

NV Bekaert SA  
 Bekaertstraat 2  
 8550 Zwevegem  
 Belgium  
 E [paintroller.wire@bekaert.com](mailto:paintroller.wire@bekaert.com)  
 www.bekaert.com

## Make-up

	ORB32 – Orbit 32	SCZ52 – Z5/2 spool
<b>Diameter range</b>	3.00 ≤ d < 8.20 mm	Redrawn: 1.60 ≤ d < 8.00 mm Rewound: 2.80 ≤ d < 10.00 mm
<b>Weight</b>	± 1000 kg / ± 1500 kg*	± 1000 kg / ± 1500 kg*
<b>Inside Ø</b>	± 550 mm	± 550mm
<b>Outside Ø</b>	± 1000mm	± 800/900mm / ± 1100/1200mm*
<b>Height</b>	± 800 mm / ± 1200 mm*	± 700mm
<b>Products</b>	Hard Grade I Hard Grade II	
<b>Load unit</b>	Loose	

\* On special request

(Available for both the Orbit 32 and Z5/2 spool)



Unwrapped



Wrapped in tisscoat



Wrapped in tisscoat + hardboard



SCZ52 – Z5/2 spool

### Modifications reserved.

All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. © Bekaert 2011