



<b>EC Declaration of Performance</b> <b>DRAMIX® 4D 65/60BG</b>	<b>CUSTOMER INFORMATION</b>
<p>1. Unique identification code of the product: <b>DRAMIX® 4D 65/60BG</b></p> <p>2. Intended use : DRAMIX® 4D 65/60BG are steel fibres, made of cold-drawn wire, for STRUCTURAL USE in concrete, mortar and grout.</p> <p>3. Manufacturer: NV BEKAERT SA Bekaertstraat 2, B-8550 Zwevegem, Belgium</p> <p>5. System of assessment and verification of constancy of performance of the construction product: System n°1</p> <p>6a. Harmonized Standard: EN 14889-1: 2006. Notified Body: BCCA - registration nr: 0749 / B-1040 Brussels, Aarlenstraat - Rue d' Arlon, 53 TZUS - registration nr: 1020 / CZ-19000 Praha 9, Proseckà 811/76a</p> <p>7. Declared performance: the essential characteristics per product type are listed in table 1.</p> <p>The performance of the products above and listed in table 1, is in conformity with the declared performance in point 7. This declaration of performance is issued, in accordance with regulation (EU) N°305/2011 under the sole responsibility of the manufacturer identified above.</p> <p>Signed for and on behalf of the manufacturer by: Eric Peeters, Divisional CEO Sustainable Construction - NV Bekaert SA</p>	
<p>Approved by: Eric Peeters</p> <p>Issued and signed on version date, Zwevegem–Belgium</p> 	

Disclaimer: This Customer Information shall not constitute a guarantee for any specific use of the product. Final determination of suitability of this material is the sole responsibility of the user.

<b>EC Declaration of Performance</b> <b>DRAMIX® 4D 65/60BG</b>	<b>CUSTOMER</b> <b>INFORMATION</b>
---	---------------------------------------

Addendum to pt 7. Declared Performance on essential characteristics – see table 1

Table 1: Declaration on essential characteristics in accordance with EN 14889-1: 2006.	
Product type	DRAMIX® 4D 65/60BG
EC Certificate of constancy of performance Issued by notified body	BC1-251-0024-0056-xxx; 1020-CPR-010034xxx
Fibre shape	multi - hooked ends
Bundling	Glued
Coating	-
Length (mm)	61
Diameter (mm)	0,90
Aspect Ratio	68
Tensile Strength (N/mm <sup>2</sup> )	1600
Effect on consistence (s)	8
Effect on strength of concrete (kg/m <sup>3</sup> )	10
Release of dangerous substances	No
Durability	NPD
Modulus of elasticity (GPa)	210

Disclaimer: This Customer Information shall not constitute a guarantee for any specific use of the product. Final determination of suitability of this material is the sole responsibility of the user.