

CE ydeevnedeklaration Wiremix® W40

KUNDE INFORMATION

1. Varetypens unikke identifikationskode: **Wiremix® W40**
2. Tilsigtet anvendelse:
Wiremix® W40 er stålfibre fremstillet af koldtrukket wire til **ANDEN ANVENDELSE** i beton, mørtel og cementmørtel.
3. Fabrikant: NV BEKAERT SA Bekaertstraat 2, B-8550 Zwevegem, Belgium.
5. System for vurdering og kontrol af konstansen af byggevarens ydeevne:
System nr. 3
- 6a. Harmoniserede Norm: EN 14889-1: 2006.
7. Deklareret ydeevne:
De væsentlige egenskaber for hver produkttype findes i tabel 1.

Ydeevnen af de produkter, der er anført herover og angivet i tabel 1, opfylder den erklærede ydeevne i punkt 7.
Denne erklæring om ydeevne er udstedt i overensstemmelse med forordning (EU) nr. 305/2011 med ovennævnte producent som eneste ansvarlig.

Underskrevet for og på vegne af producenten af:
Raf Rentmeesters, Senior Vice President Building Products - NV Bekaert SA

Approved by:
Raf Rentmeesters



Issued and signed on version date, Zwevegem-Belgium



Disclaimer: This Customer Information shall not constitute a guarantee for any specific use of the product. Final determination of suitability of this material is the sole responsibility of the user.

CE ydeevnedeklaration Wiremix® W40

KUNDE INFORMATION

Tillæg til pkt. 7. Erklæret ydeevne vedrørende vigtige egenskaber - se tabel 1

Tabel 1: Erklæring vedrørende vigtige egenskaber i henhold til EN 14889-1: 2006.	
Produkt type	Wiremix® W40
CE attest for byggevarens ydeevnekonstansUdstedt af notificeret organ	-
Fiberform	Korrugerede
Bundtning	løs
Overfladebehandling	no
Længde (mm)	37 - 43
Diameter (mm)	0,75 - 1,45
L/D-forhold	28-53
Trækstyrke (N/mm ²)	≥ 700
Effekt på konsistens (s)	8
Effekt på betonstyrke (kg/m ³)	35
Frigivelse af farlige stoffer	No
Bestandighed	NPD
Elasticitetsmodul (GPa)	200

Disclaimer: This Customer Information shall not constitute a guarantee for any specific use of the product. Final determination of suitability of this material is the sole responsibility of the user.