

## EC Declaration of Performance Synmix® SP 55

## CUSTOMER INFORMATION

- 1. Unique identification code of the product: Synmix® SP 55
- Intended use : Synmix® SP 55 are polymer fibres for OTHER USES in concrete, mortar and grout. (class II - macro fibres)
- 3. Manufacturer: NV BEKAERT SA Bekaertstraat 2, B-8550 Zwevegem, Belgium
- 5. System of assessment and verification of constancy of performance of the construction product: System n°1
- 6a. Harmonized Standard:EN 14889-2: 2006
  Notified Body:
  TZUS registration nr: 1020 / CZ-19000 Praha 9,Proseckà 811/76a
- 7. Declared performance: the essential characteristics per product type are listed in table 1.

The performance of the products above and listed in table 1, is in conformity with the declared performance in point 7.

This declaration of performance is issued, in accordance with regulation (EU) N°305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Raf Rentmeesters, Senior Vice President Building Products - NV Bekaert SA

Approved by: Raf Rentmeesters



Issued and signed on version date, Zwevegem-Belgium

Disclaimer: This Customer Information shall not constitute a guarantee for any specific use of the product. Final determination of suitability of this material is the sole responsibility of the user.

DOP\_CI.00010.BKZW/version 3:2022/10/03 Replaces: v2 2020/07/07 Creationdate: 2023/10/10 – Language EN Page 1/2 Electronically approved Building Products//Geert Demeyere



## EC Declaration of Performance Synmix® SP 55

## Addendum to pt 7. Declared Performance on essential characteristics - see table 1

Table 1: Declaration on essential characteristics in accordance with EN 14889-2: 2006	
Product type	SP 55
EC Certificate of constancy of performance	1020-CPR-010047173
Fibre shape	corrugated wavy
Bundling	loose
Coating	Νο
Length (mm)	55
Diameter (mm)	0,85
Aspect Ratio	65
Tensile Strength (N/mm²)	365
Effect on consistence (s)	11
Effect on strength of concrete (kg/m <sup>3</sup> )	8
Modulus of elasticity (N/mm <sup>2</sup> )	4800
Polymer Type	Class II - macro fibres
Melting point (°C)	165
Point of ignition (°C)	≥ 330
Release of dangerous substances	Νο
Durability	NPD

Disclaimer: This Customer Information shall not constitute a guarantee for any specific use of the product. Final determination of suitability of this material is the sole responsibility of the user.

Building Products//Geert Demeyere