

Dramix® 3D

80/30SL

Aspect ratio

Length

Stainless

Loose

Concrete Reinforcement



Original anchorage

Dramix® 3D is the cost-efficient fiber for standard statically indeterminate concrete structures that are subjected to regular static, fatigue and dynamic loadings.

Material properties

Nom. tensile strength:

#N/A ksi (#N/A MPa)

Young's modulus:

30,458 ksi (210.000 MPa)

Strain at ultimate strength:

0.8 %

Fiber network

16,205 fibers/lb (35,726 fibers/kg)

Geometry

Fiber family



Length (l) * / Diameter



Aspect ratio (l/d) * : 80

* Indicative value


Packaging

BAGS:

44 lb
(20 kg)



Handling



NO STACKING



KEEP DRY

Product certificates*



System certificates*

Dramix® plants are ISO 9001 and ISO 14001 certified.



Product conformity

Dramix conforms to:
ASTM A820-type I,
EN 14889-1,
ISO 13270 class A

Contact us:

For inquiries and orders on <https://construction.bekaert.com/contact-us>



For recommendations on stacking, handling, dosing and mixing, visit <https://construction.bekaert.com/dosing>

Any other specific document or certificate can be found on <https://construction.bekaert.com/resources>

* Product and system certificates are plant specific.