

Dramix[®] 3D

80/30SL

Aspect ratio Length Stainless Loose

Concrete Reinforcement



Original anchorage

Dramix[®] 3D is the cost-efficient fiber for standard statically indeterminate concrete structures that are subjected to regular static, fatigue and dynamic loadings.

Material properties

Nom. tensile strength:
#N/A ksi (#N/A MPa)
Young's modulus:
30,458 ksi (210.000 MPa)
Strain at ultimate strength:
0.8 %

Fiber network

16,205 fibers/lb (35,726 fibers/kg)

Geometry

Fiber family



Length (l) * / Equivalent Diameter (d)

1.2 in. (30 mm)



Aspect ratio (l/d) * : 80


* Indicative value

Packaging

BAGS:
44 lb
(20 kg)



Handling



NO STACKING



KEEP DRY

Product certificates*



System certificates*

Dramix[®] plants are ISO 9001 and ISO 14001 certified.



Product conformity

Dramix conforms to:
ASTM A820 type I, EN 14889-1,
ISO 13270 class A
Intended for use in concrete
complying with ASTM C1116,
Section 4.1.1

Contact us:

For inquiries and orders on
<https://construction.bekaert.com/contact-us>



For recommendations on stacking, handling,
dosing and mixing, visit
<https://construction.bekaert.com/dosing>

Any other specific document or certificate
can be found on
<https://construction.bekaert.com/resources>

* Product and system certificates are plant specific.