

Dramix® 3D

80/60BL

Aspect ratio

Length

Bright

Loose

Concrete Reinforcement



Original anchorage

Dramix® 3D is the cost-efficient fiber for standard statically indeterminate concrete structures that are subjected to regular static, fatigue and dynamic loadings.

Material properties

Nom. tensile strength:

178 ksi (1,225 MPa)

Young's modulus:

30,458 ksi (210,000 MPa)

Strain at ultimate strength:

0.8 %

Fiber network

2,127 fibers/lb (4,690 fibers/kg)

Geometry

Fiber family



Length (l) * / Diameter

2.4 in. (60 mm)



Aspect ratio (l/d) * : 80

* Indicative value

Packaging


BAGS:

44 lb

(20 kg)



Handling



NO STACKING



KEEP DRY

Product certificates*



System certificates*

Dramix® plants are
ISO 9001 and
ISO 14001 certified.



Product conformity

Dramix conforms to:

ASTM A820-type I,

EN 14889-1,

ISO 13270 class A

Contact us:

For inquiries and orders on

<https://construction.bekaert.com/contact-us>



For recommendations on stacking, handling,
dosing and mixing, visit

<https://construction.bekaert.com/dosing>

Any other specific document or certificate
can be found on

<https://construction.bekaert.com/resources>

* Product and system certificates are plant specific.