




Lashing Wire Datasheet

Bekaert Lashing wire provides flexibility, strength, and corrosion resistance required for supporting fiber optic cables in Outside Plant (OSP) telecommunications projects. The product meets the requirements per ASTM A580 and works with most cable lashers.



Specifications, per ASTM A580

| AISI Grade | UNS | W.Nr | Wire Diameter (in) | Weight per coil (lb) | Length per coil (ft) | Average break strength (lb) | Coils per box | Approx. shipping weight per box (lb) |
|------------|--------|--------|--------------------|----------------------|----------------------|-----------------------------|---------------|--------------------------------------|
| 430 SS | S43000 | 1.4016 | 0.045 | 6.5 | 1,200 | 125 | 6 | 40 |
| 302 SS | S30200 | 1.4310 | 0.038 | 6.3 | 1,600 | 115 | 6 | 38 |
| 302 SS | S30200 | 1.4310 | 0.045 | 6.5 | 1,200 | 165 | 6 | 40 |
| 316 SS | S31600 | 1.4401 | 0.045 | 6.5 | 1,200 | 165 | 6 | 40 |
| 316 SS | S31600 | 1.4401 | 0.038 | 6.3 | 1,600 | 115 | 6 | 38 |

Pack specifications

Coil Dimensions

| | |
|--------|------------|
| ID | 1 5/8" min |
| OD | 5 3/8" max |
| Height | 2" max |

Box Dimensions

| | |
|---------------|--------|
| Coils per box | 6 |
| Width | 5 1/2" |
| Length | 11" |
| Height | 5 1/2" |

Pallet Dimensions

| | |
|------------------|-----|
| Boxes per pallet | 63 |
| Width | 33" |
| Length | 42" |
| Height | 26" |

Finish: Bright annealed

ISO
9001:2015
certified



Contact Us

More
Information?

1395 South Marietta Parkway,
Building 500, Suite 100
Marietta, Georgia 30067, USA
770.514.2219

www.bekaert.com/power-utilities

Modifications reserved.

All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. ©Bekaert 2022