BEKAERT

better together

Reliable support that gives you peace of mind

Bezinal[®] fruit support and protection

Benefits

Premium quality to protect your fruits





Low maintenance and higher vield return

Why choose **Bekaert?**

Advanced steel wire and coating solutions

leader in steel wire transformation and coating technologies. We have been producing steel wire solutions for over 130 years, meeting the need of a wide range of industries.

Ready to protect your fruits

No matter how the weather is: heavy rain, strong wind or hail, you want your investment to be well protected.

Rely on a stable, low-maintenance wire system that will not sag or break. Even under the most severe weather conditions, our Bezinal® coating has proven to outperform traditional wires.

Lifetime support and service

From planting your fruit trees until harvesting, you should trust a wire support system that helps you to take care of your orchards.

It's designed for easy installation, as well as easy maintenance while still providing strong support for the entire lifetime of your fruit trees.

Low maintenance and higher yield return

Due to its low elongation, your wire trellis will require less maintenance. Even with a lower diameter, our Bezinal® wire solutions provide you that same tensile strength as with a higher diameter than traditional solutions.

You will save time and money and in the end, you can increase your yield return by simply choosing Bezinal® Wire solutions system for your fruit growing systems.







Your strategic partner

Our global presence means that your products are manufactured to strict international standards of safety and quality. Our local contact us via info.agri@bekaert.com; a trained possible.

Whatever your application, we will work closely with you. Together, we will create a lasting solution that answers your need.

Comparison Bezinal® fruit tensioning vs. ordinary / heavy galvanized wires

Ordinary / Heavy Galvanised TS 400/500 N/MM²

JDP	Ø in mm	BL in kg	Length in m
11	1,6	95	± 1580
12	1,8	120	± 1250
13	2,0	150	± 1000
14	2,2	180	± 825
15	2,4	215	± 650
16 (2,7)	2,8	290	± 520
17	3,0	335	± 450
18 (3,4)	3,5	450	± 530
19 (3,9)	4,0	595	± 400
20 (4,4)	4,5	755	± 320
21 (4,9)	5,0	930	± 260
22 (5,4)	5,5	1125	± 215
24 (6,4)	6,5	1575	± 150

Fruit tensioning and anti-hail TS 1100/1300 N/MM²

Ø in mm	BL in kg	Length in m
1,6	240	± 1580
1,8	300	± 1250
2,0	380	± 1000
2,2	460	± 825
2,5	590	± 650
2,8	830	± 520
3,1	955	± 420
3,5	1155	± 330
4,1	1585	± 240

Fruit tensioning and anti-hail TS 1250/1450 N/MM²

Ø in mm	BL in kg	Length in m
2,0	420	± 1000
2,2	510	± 825
2,5	660	± 650
2,8	830	± 520
3,0	955	± 420
3,5	1300	± 330
3,8	1530	± 280
3,9	1610	± 260
4,0	1700	± 250

All diameters in the table are for comparison. To see our full diameter range, please contact us: info.agri@bekaert.com

Wrapping test at Bekaert Technology Center Deerlijk

When asking customers, one of the most important elements of wire solutions is to **easily bend or twist by hand without having any cracks.** Especially when doing the re-tensioning of the trellises, it contributes to the ease of maintenance.

At our **technology center in Deerlijk, we performed a wrapping test** where our Bezinal[®] fruit tensioning and protection wires and other types of tensioning wires were twisted around their axes at a speed of 1 round per second.When comparing both results under a microscope with a magnifying rate of 80x, the photo of our Bezinal[®] wires shows significantly fewer cracks than other traditional wires.



Aailable make-ups

RWC & CWC of 25kg, 40 kg or 100kg



More information?

Bekaert.com/fruitsupportandprotection



NV Bekaert SA Bekaertstraat 2 B-8550 Zwevegem info.agri@bekaert.com Modifications reserved. All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. © Bekaert 2022

Responsible editor: NV Bekaert SA - 7 2022