

better together

Wiper component wire



Pre-coated wire with good formability for more efficient processing

Why choose Bekaert?

The specialist in wire rod selection

Bekaert has a vast network of top suppliers and years of experience in selecting only the highest quality wire rod. In total, we use over 50 alloy qualities ranging in diameter from 5.5 mm to 25 mm.

Flexible production

To accommodate a broad range of applications, Bekaert offers a wide range of common and specialised production processes. Depending on the required properties, the classic production process of cleaning, drawing, thermal treatment, shaping, coating and winding can be combined in order to obtain the wire you need.



Global presence

Bekaert is active in more than 120 countries and employs over 23 000 people worldwide. This makes us the largest independent wire manufacturer in the world, selling wire to almost all countries.

4. 600 international experts at your disposal

Bekaert's technology centers count over 600 international experts who have the technical know-how and experience to create the wire and coating that meets your expectations.

Coated wires and materials

Improve your production process thanks to the unique coatings and excellent formability of Bekaert's wiper component wire.

	Bezinal®	Bezinal [®] Color	Bezalplast [®]	Bekinox®
Composition	Fe (Zn+Al)	Fe Colour (Zn+Al)	Fe PET	Stainless steel
Corrosion resistance	+	+	++	+++
Colour	not applicable	+	++	+
Formability	++	+	++	++
Discover the benefits :	 Excellent corrosion resistance: 2 to 3 times better than zinc for the same coating weight. Improved cathodic protection 	White rust protection Colour	 Superior corrosion resistance Coloured alternative for stainless steel wire 	

Looking for a specific coating or shape? Contact your local Bekaert specialist. (contact details on the back)



Product range

Flat blade wire

Patented hardrolled SAE 1065-1078 Bezalplast® coated wire

• Standard sizes: - for front & rear wiper: 7.17x1.03 mm (0.275x0.040 inch)

- for rear wipers only: 4.35x0.80 mm (0.275x0.048 inch)

Other dimensions available on request.

• Tensile strength : 1850-2050 N/mm²

Wiper blade wire

Standard quality :

AISI 310, 302, 204Cu,... cold rolled wire

- Standard sizes: 2.50x0.80 mm (0.098x0.031 inch)
 - 2.50x0.70 mm (0.098x0.028 inch) 2.50x0.60 mm (0.098x0.024 inch)
 - 2.80x0.70 mm (0.110x0.028 inch)
- Tensile strength : 1600-1800 N/mm²

Patented SAE 1055-1065 Bezinal® coated cold rolled wire

- Standard sizes: 4.20x1.00 mm (0.165x0.039 inch)
 - 4.00x1.20 mm (0.157x0.047 inch)
- Tensile strength : 1600-1800 N/mm²

Patented SAE 1060-1070 Bezinal® Color coated cold rolled wire

- Standard sizes: 2.50x0.80 mm (0.098x0.031 inch) 2.80x0.80 mm (0.110x0.031 inch)
- Tensile strength : 1600-1800 N/mm²
- Standard colors : Transparent or black

Wiper arm wire

Global market

SAE 1035-1045 patented, Bezinal® coated, cold rolled wire

- Standard sizes: 9.00x3.90 mm (0.354x0.153 inch) 9.00x3.30 mm (0.354x0.130 inch) 9.00x4.00 mm (0.354x0.157 inch) 12.00x4.00 mm (0.354x0.157 inch)
- Tensile strength : 1000-1200 N/mm²

US market

SAE 1018-1035 spherodized annealed, Bezinal® coated, cold rolled wire

 Standard sizes: 	9.00x3.90 mm	(0.354x0.153 inch)
	9.00x3.30 mm	(0.354x0.130 inch)
	9.00x4.00 mm	(0.354x0.157 inch)
	12.00x4.00 mm	(0.354x0.157 inch)

Tensile strength : 110-130 ksi


Wiper spring wire

Standard quality :

- Patented, Bezinal[®] coated harddrawn SAE 1077-1087 spring wire
- Sizes: 1.80 up to 4.00 mm (0.070 up to 0.157 inch)
- Tensile strength : EN 10270-1 SH
- Phosphate coated harddrawn SAE 1082 spring wire
- Sizes: 3.00 and 2.60 mm (0.118 and 0.102 inch)
- Tensile strength 264-291 ksi and 270-299 ksi according to ASTM A228











better together

Supporting your business world wide

Bekaert is a global market leader in drawn steel wire products and coating solutions. With 130 years experience, a solid working knowledge of the international trade markets and a global network of resources and sales offices Bekaert is able to assist customers in more than 120 counties. Working better together Bekaert can bring the quality it is known for around the world, to your business.

Global contact details available on www.bekaert.com



Modifications reserved.

All details describe our products in general form only. For ordering and design only use official specifications and documents. Unless otherwise indicated, all trademarks mentioned in this brochure are registered trademarks of NV Bekaert SA or its subsidiaries. © 2012 Bekaert

All Bekaert plants that produce wiper component wire are ISO 9001 and ISO TS 16949 certified.

NV Bekaert SA

Bekaertstraat 2 8550 Zwevegem Belgium T +32 56 76 62 30 F +32 56 76 79 51 wiper.components@bekaert.com www.bekaert.com