


better together

# Stucanet<sup>®</sup> S E-BM Product Data Sheet

#### **Panel elements**



#### **Dimensions and weights**

Panel size (mesh, excluding breather membrane)						
Longitudinal	Transversal	Surface Net usable panel surface after over				
mm		m²/panel	m²/panel			
2395	705	1.68	Approx. 1.56 m <sup>2</sup>			

Breather membrane				
Longitudinal	Transversal			
mm				
2350	725			

Size and number of meshes						
Longitudinal	Transversal					
38 x 50 mm						
63 pcs	13 pcs		2 pcs			
Weight						
kg/panel		kg/m²				
2.03		1.20				

## **General description**

Bekaert Stucanet<sup>®</sup> S E-BM is a purpose designed plaster and render carrier manufactured from a stainless steel welded wire mesh into which a moisture absorbent sheet of chip paper is interwoven. The chip paper assists with the wet adhesion and curing of the mortar and the perforations allow the mortar to perfectly bond around the steel wires, resulting in firm anchoring of the mortar and high resistance to load and impact.

Stucanet<sup>®</sup> S E-BM has two parallel, round fixing wires.

Stucanet<sup>®</sup> S E-BM is used specifically for exterior facade applications. It has the same wire structure as Stucanet<sup>®</sup> S, but is protected with a breather membrane to prevent moisture penetration whilst still allowing the wall to breathe naturally.

For further details, please contact us or ask for the Stucanet<sup>®</sup> application instructions.



### **Technical specifications**

Wire diameters						
Fixing wire	Longitudinal wire	Cross wire				
mm	mm (diameter)	mm (diameter)				
1.50 and 2.00	1.50	1.50				
Stainless steel type						
Fixing wire	Longitudinal wire	Cross wire				
gr/m²	gr/m²	gr/m²				
Austhenitic stainless steel						
Tensile strength of wires						
Fixing wire	Longitudinal wire	Cross wire				
N/mm <sup>2</sup>						
> 350						

# Packaging and packaging units

- Panels are packed in bundles of 15 pieces.
- The bundles are stacked on wooden pallets. For Stucanet<sup>®</sup> S E-BM, 25 bundles are stacked per pallet.
- Each bundle has a product label.

lle	m²/bundle					
	25.3					
Panels per pallet		m²/pallet				
375		633				
Palet specifications						
Weight						
kg (g						
78	33	2.45 x 0.73 x 1.50				
	Panels p 37 Palet spec ght kg (c	Panels per pallet 375 Palet specifications				

## Certificates

- CE, compliant with EN 13658 - 1 and 2: 2005. The document "EC Declaration of Conformity" is available upon request.



Unless otherwise indicated, all trademarks are registered trademarks owned by NV Bekaert SA @ 2013 Bekaert

NV Bekaert SA Bekaertstraat 2 8550 Zwevegem Belgium T +32 56 76 72 92 F +32 56 76 72 90 buildingbenelux@bekaert.com www.bekaert.com/building

