

Stainless Steel Lashing Wire (BABA & Import)

Bekaert Lashing Wire delivers reliable performance for fiber broadband, telecommunications, and utility communication networks. Available in imported and fully BABA-compliant configurations, our ASTM A580-compliant lashing wire is compatible with most cable lashers. Our fully BABA-compliant lashing wire is manufactured in Van Buren, Arkansas, making Bekaert the only domestic manufacturer offering a fully BABA-compliant lashing wire solution. We provide Made & Melted certifications, traceability, and compliance documentation to help simplify procurement for federally funded and BEAD-supported projects.



Specifications, per **ASTM A580**

AISI Grade	UNS Number	W.Nr	Wire Diameter (in)	Weight per coil (lb)	Length per coil (lb)	Average break strength (lb)	Coils per box	Approx. shipping weight per box (lb)	Compliance
430SS	S43000	1.4016	0.045	6.5	1,200	125	6	40	non-BABA
302SS	S302000	1.4310	0.038	6.3	1,600	115	6	38	BABA
302SS	S302000	1.4310	0.038	6.3	1,600	115	6	38	non-BABA
302SS	S302000	1.4310	0.045	6.5	1,200	165	6	40	BABA
302SS	S302000	1.4310	0.045	6.5	1,200	165	6	40	non-BABA

Packaging Specifications

Coil Dimensions

ID	1 5/8" min
OD	5 3/8" max
Height	2" max

Box Dimensions

Coils per box	6
Width	5 1/2"
Length	11"
Height	5 1/2"

Box Dimensions

Boxes per box	63
Width	33"
Length	42"
Height	26"

Contact Us

4300 Wildwood Parkway,
Suite 100
Marietta, Georgia 30339, USA
(770) 906-2261
www.bekaert.com/power-utilities



ISO
9001:2015
certified

