

**EC Declaration of Performance  
Mesh Track®**

**CUSTOMER  
INFORMATION**

1. Unique identification code of the product: **Mesh Track®**  
with different product types and width - see table 1.
2. Intended use: in accordance with **EN 15381:2008**  
Metallic, geotextile-related product as reinforcement for pavements and asphalt overlays – R.
3. Manufacturer: **NV BEKAERT SA Bekaertstraat 2, 8550 Zwevegem, Belgium.**
5. System of assessment and verification of constancy of performance of the construction product:  
**System 2+**
- 6 a. Harmonised standard: EN 15381:2008  
Notified Body: n° 1301-CPR - TSUS, SK-824 04 Bratislava, Studená 3
7. Declared performance:  
the essential characteristics per product type are listed in table 1.

The performance of the product identified above, is in conformity with the declared performance in point 7. This declaration of performance is issued, in accordance with regulation (EU) N° 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Raf Rentmeesters, Senior Vice president Building products, *NV Bekaert SA*

## EC Declaration of Performance Mesh Track®

## CUSTOMER INFORMATION

Addendum to pt 7. Declared Performance on essential characteristics – see table 1

in accordance with **EN 15381:2008**

Table 1: Declared Performance on essential characteristics per Mesh Track® product type.

Essential characteristic	Unit of measure	Mesh Track® 1	Mesh Track® 2
Mesh Tensile strength:			
MD	kN/m	40.0 -1.0/+3.0	32.0 -1.0/+3.0
CMD	kN/m	50.0 -1.0/+4.0	34.0 -1.0/+4.0
Mesh Elongation at max.force:			
MD	%	19.0 ± 2	19.0 ± 2
CMD	%	2.0 -1.0/+0.5	2.0 -1.0/+0.5
Durability: corrosion resistance		Coating Zn95Al5 (EN10244-2)	
Round mesh wire			
Reinforcement wire			

**Disclaimer :** This Customer Information shall not contribute a guarantee for any specific product features. Final determination of suitability of this material is the sole responsibility of the user.